



Базовая комплектация

		Модель	Мощность (л.с. / об/мин)	Расход (л/100 км)	Объем (см3)	Разгон (сек.)	€
CLUBMAN (R55)		Cooper	122/6000	5.5	1598	9.8	25 941
		Cooper S	184/5500	5.9	1598	7.5	32 377
		JCW	211/6000	7.3	1598	7.3	39 436
		Cooper D	112/4000	3.9	1598	10.4	28 236
		Cooper D AT	112/4000	5.3	1598	10.9	30 075
		Cooper SD	143/4000	4.5	1995	8.9	33 598
HATCH (R56)		One	98/6000	5.4	1598	10.5	21 657
		Cooper	122/6000	5.4	1598	9.1	23 894
		Cooper S	184/5500	5.8	1598	7.0	30 124
		JCW	211/6000	7.1	1598	6.5	37 248
		One D	90/4000	3.8	1598	11.4	23 599
		Cooper D	112/4000	3.8	1598	9.7	25 941
		Cooper D AT	112/4000	5.1	1598	10.1	27 782
		Cooper SD	143/4000	4.3	1995	8.1	31 347
CONVERTIBLE (R57)		Cooper	122/6000	5.7	1598	9.8	28 910
		Cooper S	184/5500	6.0	1598	7.3	35 379
		JCW	211/6000	7.3	1598	6.8	41 503
		Cooper D	112/4000	3.8	1598	10.3	30 912
		Cooper D AT	112/4000	5.1	1598	10.8	32 750
		Cooper SD	143/4000	4.3	1995	8.7	36 612
COUPE (R58)		Cooper	122/6000	5.4	1598	9.0	25 843
		Cooper S	184/5500	5.8	1598	6.9	32 073
		JCW	211/6000	7.1	1598	6.4	39 161
		Cooper D	112/4000	3.8	1598	9.7	33 294
ROADSTER (R59)		Cooper	122/6000	5.7	1598	9.2	27 771
		Cooper S	184/5500	6.0	1598	7.0	34 239
		JCW	211/6000	7.3	1598	6.5	40 364
		Cooper D	112/4000	3.8	1598	10.1	35 471
COUNTRYMAN (R60)		One	98/6000	6.0	1598	11.9	25 159
		Cooper	122/6000	6.0	1598	10.5	26 927
		Cooper ALL4	122/6000	6.5	1598	10.9	28 974
		Cooper ALL4 AT	122/6000	7.0	1598	11.3	30 821
		Cooper S	184/5500	6.1	1598	7.6	32 096
		Cooper S ALL4	184/5500	6.7	1598	7.9	31 740
		JCW ALL4	218/6000	7.5	1598	7.0	42 190
		One D	90/4000	4.4	1598	12.9	27 497
		Cooper D	112/4000	4.4	1598	10.9	28 930
		Cooper D ALL4	112/4000	4.9	1995	11.6	30 760
		Cooper D AT	112/4000	5.6	1598	11.3	30 977
		Cooper D All4 AT	112/4000	6	1995	11.8	32 807
		Cooper SD	143/4000	4.6	1995	9.3	33 181
		Cooper SD ALL4	143/4000	4.9	1995	9.4	35 228
PEACEMAN (R61)		Cooper	122/6000	6.0	1598	10.4	28 376
		Cooper ALL4	122/6000	6.5	1598	10.9	30 423
		Cooper ALL4 AT	122/6000	7.0	1598	11.3	32 270
		Cooper S	184/5500	6.1	1598	7.5	33 546
		Cooper S ALL4	184/5500	7.1	1598	7.8	35 592
		JCW ALL4	218/6000	7.4	1598	6.9	43 639
		Cooper D	112/4000	4.4	1598	10.8	30 379
		Cooper D ALL4	112/4000	4.9	1995	11.5	32 426
		Cooper D AT	112/4000	5.6	1598	11.2	32 209
		Cooper D AT ALL4	112/4000	6	1995	11.8	34 256
		Cooper SD	143/4000	4.6	1995	9.2	34 631
		Cooper SD ALL4	143/4000	4.9	1995	9.3	36 678